#### **HyPanel Pro**

#### New hassle-free smart control panel for your home

The akubela HyPanel Pro, a smart control panel with an Android 10 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway and home automation, and is compatible with plentiful ecosystem. Minimalist exterior design, allowing users to enjoy a higher quality communication experience. Support infrared remote control function, intelligent control of traditional home appliances, to achieve a more outstanding smart home experience.

#### At a Glance

- inch touchscreen
- Metal frame with a decorative strip available in various colors and textures
- Built in with multiple sensors
- Support infrared remote control
- Android 10 OS powered by a high-performance Qualcomm chip
- Intercom, ZigBee gateway, and smart home control panel in one device



#### **Basic Information**

- Model Number: PG71N-PoE-US
- Power Supply: IEEE802.3af PoE & 12-24VDC
- RS485 Port: Support
- Operation System: Android 10
- RAM/ROM: 2GB/16GB
- Wi-Fi: IEEE802.11 b/g/n/ac, @2.4GHz/5GHz
- Bluetooth: Bluetooth 4.2
- Ethernet Port: 1×RJ45, 10/100Mbps adaptive
- ZigBee: ZigBee 3.0
- Infrared Remote Control: Support

- Microphone: Dual microphones, -38dBV
- Speaker: Single speaker,  $6\Omega/1.8W$

#### Appearance

- Material: Metal
- Screen: 8" multi-touch screen, AF hydrophobic anti-pollution fingerprint proof coating
- Screen Resolution: 1280×800 pixels
- Screen Brightness: 310 cd/m2

# Cakubela

10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061 Email: sales@akuvox.com Web: www.akubela.com

### HyPanel Pro

## Datasheet

### Sensors Built In

- Proximity Sensor: 30 ~ 60cm
- Light Sensor: Low-level lux detection
- Temperature Sensor:  $\pm 1^{\circ}$ C, range:  $-10 \sim 50^{\circ}$ C
- Humidity Sensor: ±5%, range: 10 ~ 90%RH, without condensation

### Working Environment

- Environment: For indoor use only
- Working Humidity: 10 ~ 90%RH, without condensation

- Working Temperature: -10 ~ 50°C
- Storage Temperature: -20 ~ 70°C


### Installation

- Installation: Wall flush mounting
- Flush Mounted Module: US standard

### Application Scenario

- Villas
- Apartment complexes
- Home automation systems
- Modern interiors


## Product Dimension Diagram(mm)




5 BOTTOM VIEW




2 RIGHT VIEW



1 FRONT VIEW







(4) BACK VIEW

📿 akubela

10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061 Email: sales@akuvox.com Web: www.akubela.com